

View Online at <https://aerobasegroup.com/nsn/5935-01-089-9820>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.650 inches

Overall Height:

0.712 inches

Overall Width:

0.250 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof

Distance Between Mounting Facility Centers:

1.450 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.130 inches

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, grade c, cl 1 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Jackscrew type-male and location-left hand and jackscrew type-female and location-right hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-55302/64 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.