

View Online at https://aerobasegroup.com/nsn/5935-01-090-3162

Thread Class: 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand and right-hand **Body Style:** Straight shape **Overall Height:** 0.890 inches **Overall Width:** 1.016 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 1.953 inches **Threaded Device Type:** Coupling facility and mounting stud Mating End Quantity: 1 **Contact Position Arrangement Style:** 14 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 **Thread Size:** 0.138 inches and 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end or plastic phenolic single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize and dichromate potassium **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end Shell Guide Type And Location Designator:

G slot

Electrical Receptacle Connector Body - Page 2 of 2



Color:

Black

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.