## NSN 5935-01-090-4103

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-090-4103 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Overall Length:** 1.710 inches **Overall Height:** 1.031 inches **Overall Width:** 0.520 inches **Mounting Hole Diameter:** 0.125 inches **Body Mounting Hole Accommodation Length:** 1.075 inches **Body Mounting Hole Accommodation Width:** 0.520 inches **Distance Between Mounting Facility Centers:** 1.406 inches **Mounting Hole Style:** Rectangular, w/two mounting holes/slots **Contact Maximum Current Rating In Amps:** 13.0 **Contact Material:** Copper alloy **Contact Surface Treatment:** Gold and nickel **Accommodated Contact Quantity: Projection Length Below Mounting Surface:** 0.718 inches **Mounting Method:** Threaded stud **Mounting Type For Which Designed:** Chassis Thready Qty Per Inch (tpi): 40

40 **Thread Size:**0.112 inches

## NSN 5935-01-090-4103

Plug-in Electronic Components Socket - Page 2 of 2



| <b>Contact Position Arrangement Style:</b> |
|--------------------------------------------|
| Dual in line                               |
| Precious Material And Location:            |
| Contact surfaces gold                      |
| Precious Material And Weight:              |
| 0.008 gold grains, troy                    |
| Precious Material:                         |
| Gold                                       |
| Thread Series Designator:                  |
| Unc                                        |
| Terminal Type And Quantity:                |
| 8 tab, solder lug                          |
| Shelf Life:                                |
| N/a                                        |
| Unit Of Measure:                           |
|                                            |
| Demilitarization:                          |
| No                                         |
| Fiig:                                      |
| A02300                                     |