## NSN 5935-01-090-4134

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-090-4134 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.709 inches **Overall Diameter:** 1.954 inches **Distance From Mounting Shoulder To Front Face:** 0.879 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-090-4134

Electrical Receptacle Connector - Page 2 of 2



| Shell Material:   |
|---|
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium   |
| Shell Surface Treatment Specification:                                    |
| Qq-p-416 type ii, class 3 federal specification single treatment response |
| Included Contact Quantity:  |
| 19 single mating end single contact grouping                              |
| Included Contact Type:  |
| Round socket single mating end single contact grouping                    |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.019 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Unef  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
|   |