## NSN 5935-01-090-4136

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-090-4136

**Body Style:** Single card type **Overall Length:** 3.400 inches **Overall Height:** 1.185 inches **Overall Width:** 0.340 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof **Distance Between Mounting Facility Centers:** 2.600 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Insert Material Specification:** Mil-m-14 ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 48 single mating end single contact grouping **Included Contact Type:** Hermaphrodite single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold

0.048 gold grains, troy

**Precious Material And Weight:** 

## NSN 5935-01-090-4136

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.