

View Online at <https://aerobasegroup.com/nsn/5935-01-091-1861>

Body Style:

Straight type

Overall Length:

6.220 inches

Overall Width:

0.366 inches

Environmental Protection:

Vibration resistant

Distance Between Mounting Facility Centers:

5.900 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 2 federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Pin single mating end all contact groupings

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end all contact groupings or qq-c-530 federal specification single material response single mating end all contact groupings

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

33 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.160 gold grains - tray

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.