## NSN 5935-01-091-3527

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-091-3527

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.073 inches and 2.103 inches

**Overall Height:** 

0.653 inches

**Overall Width:** 

Between 0.479 inches and 0.509 inches

**Environmental Protection:** 

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 1.847 inches and 1.857 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

44 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Metal

# NSN 5935-01-091-3527

Electrical Receptacle Connector - Page 2 of 2



Shell Surface	Treatment:
---------------	------------

Cadmium and chromate

## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 2nd material response single mating end

## **Included Contact Quantity:**

44 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.044 gold grains, troy

## **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-24308/6 government specification

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.