## NSN 5935-01-091-7365

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-091-7365
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 2.300 inches and 2.320 inches
Overall Diameter:
Between 1.365 inches and 1.385 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
4a-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
12
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1,
grade b federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:

Solder well single mating end single contact grouping

## **NSN 5935-01-091-7365**Electrical Plug Connector - Page 2 of 2

**Shell Material:** 



Shell Surface Treatment: Cadmium Shell Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Insert Material Specification: Mil-m-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification response single mating end Included Contact Quantity:  5 single mating end single contact grouping	iication single
Shell Surface Treatment Specification:  Qq-p-416, type 2, cl 3 federal specification single treatment response  Insert Material Specification:  Mil-m-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification response single mating end  Included Contact Quantity:  5 single mating end single contact grouping	fication single
Qq-p-416, type 2, cl 3 federal specification single treatment response  Insert Material Specification:  Mil-m-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification response single mating end  Included Contact Quantity:  5 single mating end single contact grouping	fication single
Insert Material Specification:  Mil-m-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification response single mating end material response single mating end  Included Contact Quantity:  5 single mating end single contact grouping	fication single
Mil-m-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification single material response single mating end  Included Contact Quantity:  5 single mating end single contact grouping	fication single
material response single mating end  Included Contact Quantity:  5 single mating end single contact grouping	fication single
Included Contact Quantity: 5 single mating end single contact grouping	
5 single mating end single contact grouping	
Included Contact Type:	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.025 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	