## NSN 5935-01-091-7982

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-091-7982

**Body Style:** Right angle type **Overall Length:** 6.060 inches **Overall Height:** 0.445 inches **Overall Width:** 0.415 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.098 inches **Distance Between Mounting Facility Centers:** 5.300 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping **Included Contact Quantity:** 104 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping

Contact surfaces gold

**Precious Material And Location:** 

## NSN 5935-01-091-7982

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.104 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.