## NSN 5935-01-091-9540

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-091-9540



**Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 0.780 inches **Overall Height:** 1.730 inches **Overall Width:** 0.330 inches **Cable Entrance Diameter:** 0.280 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 11 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp Thready Qty Per Inch (tpi): 48 **Thread Size:** 0.099 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## **NSN 5935-01-091-9540**Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Insert Material Specification:
Mil-m-14 ty sdg-f military specification single material response single mating end
Included Contact Quantity:
11 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.011 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.