

View Online at <https://aerobasegroup.com/nsn/5935-01-092-0270>

Thread Class:

2b and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.625 inches

Overall Diameter:

0.812 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

Cable Entrance Diameter:

0.100 inches

Distance From Mounting Shoulder To Front Face:

Between 0.796 inches and 0.843 inches

Mounting Facility Thickness:

Between 0.045 inches and 0.160 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.438 inches and 0.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver and copper

Shell Surface Treatment Specification:

Qq-s-365 federal specification 1st treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

81349-mil-c-39012/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15504