Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-092-0271

## **Body Style:**

Straight shape, external coupling w/backshell

- **Overall Length:**
- 0.697 inches

## **Overall Height:**

1.047 inches

- **Overall Width:**
- 1.047 inches
- Center To Center Distance Between Mounting Facilities Parallel To Height:
- 0.406 inches
- Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
- 0.406 inches
- **Distance From Mounting Shoulder To Front Face:**
- 0.447 inches
- Mating End Quantity:
- 1
- Contact Removability:
- Removable single mating end single contact grouping
- Contact Maximum Ac Voltage Rating In Volts:
- 500.0 single mating end single contact grouping
- Contact Maximum Dc Voltage Rating In Volts:
- 700.0 single mating end single contact grouping
- **Polarization Method:**
- Keyway or multiple keyway
- Insert Position In Deg:
- 68.0
- Shell Type:
- Solid
- Connector Locking Method:
- Bayonet latch
- **Terminal Location:**
- Back single mating end single contact grouping
- **Contact Material:**
- Copper alloy single mating end single contact grouping
- **Contact Surface Treatment:**
- Gold single mating end single contact grouping
- **Terminal Type:**
- Crimp single mating end single contact grouping
- **Shell Material:**
- Aluminum alloy
- Shell Surface Treatment:
- Cadmium



Included Contact Quantity:

10 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.