

View Online at <https://aerobasegroup.com/nsn/5935-01-092-1045>

Body Style:

Straight shape, flange mount, external coupling

Overall Length:

1.438 inches

Overall Height:

0.812 inches

Overall Width:

0.812 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.594 inches

Distance From Mounting Shoulder To Front Face:

Between 0.431 inches and 0.441 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

40394 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 3 military specification single treatment response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.004 gold grains, troy and 0.004 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.