

View Online at https://aerobasegroup.com/nsn/5935-01-092-2595

| Body Style: | |
|---|---|
| Right angle type | |
| Overall Length: | |
| 6.355 inches | |
| Overall Height: | |
| 0.624 inches | |
| Overall Width: | |
| 0.343 inches | |
| Unthreaded Mounting Hole Diameter: | |
| Between 0.096 inches and 0.101 inches | |
| Distance Between Mounting Facility Centers: | |
| 6.065 inches | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 2 rows of contacts non-inserted board single mating end | |
| Contact Removability: | |
| Nonremovable single mating end single contact grouping | |
| Contact Maximum Current Rating In Amps: | |
| 3.0 single mating end single contact grouping | |
| Polarization Method: | |
| Guide pin/socket | |
| Terminal Location: | |
| Side single mating end single contact grouping | |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping | |
| Insert Material: | |
| Plastic diallyl phthalate single mating end | |
| Contact Surface Treatment Specification: | |
| Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl | 2 |
| federal specification 2nd treatment response single mating end single contact grouping | |
| Criticality Code Justification: | |
| Feat | |
| Terminal Type: | |
| Solder well single mating end single contact grouping | |
| Included Contact Quantity: | |
| 110 single mating end single contact grouping | |
| Included Contact Type: | |
| Flat socket single mating end single contact grouping | |
| Special Features: | |
| Polarizing key positions 1 and a | |
| Precious Material And Location: | |
| | |

Contact surfaces gold



Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.