## NSN 5935-01-092-4266



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-092-4266 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.718 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.282 inches **Overall Height:** 0.860 inches **Overall Width:** 1.234 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.234 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.270 inches Thready Qty Per Inch (tpi): 40

Thread Size:

0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-092-4266

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode and unable to decode
Included Contact Quantity:
75 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.075 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila

A039b0