

View Online at <https://aerobasegroup.com/nsn/5935-01-092-8159>

**Mating End Quantity:**

1

**Contact Maximum Frequency Rating:**

12400.0 megahertz single mating end single contact grouping

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Copper alloy single mating end single contact grouping and gold single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-c-14550 class 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204b type 1 grade a military specification 2nd treatment response single mating end single contact grouping and mil-g-45204b type 1 grade c class 2 military specification 3rd treatment response single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, heat treated per mil-h-7199 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Precious Material And Location:**

Contact surface gold

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-14550 spec.