NSN 5935-01-092-8163

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-092-8163

| Body Style: |
|---|
| Straight shape, external coupling |
| Overall Length: |
| 1.130 inches |
| Overall Diameter: |
| 0.690 inches |
| Environmental Protection: |
| Heat resistant and cold resistant and pressure proof and vibration resistant and shock resistant and humidity resistant |
| Distance From Mounting Shoulder To Front Face: |
| 0.800 inches |
| Mounting Facility Thickness: |
| 0.170 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bnc single mating end |
| Contact Maximum Frequency Rating: |
| 4000.0 megahertz single mating end single contact grouping |
| Shell Type: |
| Solid |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Copper single mating end single contact grouping and gold single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Copper and nickel |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| |

N/a

Shelf Life:

NSN 5935-01-092-8163

Electrical Receptacle Connector - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A039b0