

View Online at <https://aerobasegroup.com/nsn/5935-01-092-9712>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape threaded

Overall Length:

1.065 inches

Overall Diameter:

Between 2.172 inches and 2.204 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant and hermetic

Distance From Mounting Shoulder To Front Face:

Between 0.910 inches and 0.920 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

23-53 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Temperature Rating:

Between -65.0 degrees celsius and 150.0 degrees celsius

Features Provided:

Safety wire hole

Thready Qty Per Inch (tpi):

18

Thread Size:

1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Tin

Shell Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

Included Contact Quantity:

53 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Furnished items - preformed packing

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.053 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27470 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-0001-0

Mil-std (military Standard):

Mil-g-45204 spec.