## NSN 5935-01-093-2512

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-2512

**Body Style:** 

Right angle type

**Overall Length:** 

3.200 inches

**Body Height:** 

0.355 inches

**Environmental Protection:** 

Corrosion resistant and moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.140 inches

**Distance Between Mounting Facility Centers:** 

2.800 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

1 row of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1100.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

1550.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-19833, type gdi-f military specification single material response single mating end

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

11 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-093-2512

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.011 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-p-19833 spec.