Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-2528

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

0.692 inches

# **Overall Height:**

1.234 inches

# **Overall Width:**

1.234 inches

## **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.969 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.969 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.317 inches and 0.322 inches

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

16-35 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# NSN 5935-01-093-2528

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

## Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

55 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

0.055 gold grains, troy and 0.055 silver grains, troy

## **Precious Material:**

Gold and silver

## **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

96906-ms27499 government standard

Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-c-38999 spec.