

View Online at <https://aerobasegroup.com/nsn/5935-01-093-3150>

Body Style:

Angle shape, pcb type

Overall Length:

2.150 inches

Overall Height:

0.655 inches

Overall Width:

0.359 inches

Environmental Protection:

Vibration resistant and shock resistant and salt spray proof and corrosion resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification 1st material response single mating end or mil-p-46174 military specification 2nd material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Polarizing pin is a square post

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.026 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.