Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-3156

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

0.697 inches

# **Overall Height:**

1.703 inches

**Overall Width:** 

1.703 inches

## **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant

and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.142 inches and 0.157 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

1.376 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.376 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

24-61 single mating end

## Contact Removability:

Removable single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

95.0 and 132.0 and 232.0 and 260.0 and 345.0

## Shell Type:

Solid

# **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 150.0 degrees celsius

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# Terminal Type:

Crimp single mating end single contact grouping



## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium and chromate and nickel

# Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification 1st treatment response and qq-p-416, type 2 federal specification 2nd treatment response

## **Included Contact Quantity:**

61 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.061 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

96906-ms27508 government standard

# Shelf Life:

N/a

### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.