

View Online at <https://aerobasegroup.com/nsn/5935-01-093-4400>

Overall Length:

1.125 inches

Overall Diameter:

0.625 inches

Environmental Protection:

Corrosion resistant and moisture resistant and salt water resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.415 inches

Mounting Facility Thickness:

0.218 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Radio Frequency Type Contact Characteristic Impedance In Ohms:

78.0 single mating end all contact groupings

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 2 military specification single treatment response single mating end all contact groupings

Included Contact Quantity:

1 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket single mating end 2nd contact grouping

Precious Material And Location:

Contact plating gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-3655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.