## NSN 5935-01-093-4401



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-093-4401 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Distance From Mounting Shoulder To Front Face:** 0.792 inches **Mounting Facility Thickness:** 0.187 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Surface Treatment:** Silver

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

## NSN 5935-01-093-4401

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surface gold and body surface silver

**Precious Material And Weight:** 

0.005 gold grains, troy and 0.100 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0