

View Online at <https://aerobasegroup.com/nsn/5935-01-093-4409>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/cable clamp

**Overall Length:**

1.500 inches

**Bushing Diameter:**

0.505 inches

**Overall Height:**

0.700 inches

**Overall Width:**

0.700 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and thermal shock resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.496 inches and 0.504 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.496 inches and 0.504 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.535 inches and 0.565 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.099 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Specification Data:**

81349-mil-c-39012/18 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.