Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-5188

# Body Style:

Straight type

## Overall Length:

Between 4.040 inches and 4.060 inches

## **Overall Height:**

Between 0.735 inches and 0.755 inches

#### **Overall Width:**

Between 0.365 inches and 0.385 inches

## **Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.110 inches and 0.130 inches

## Distance Between Mounting Facility Centers:

Between 3.790 inches and 3.810 inches

## Mating End Quantity:

1 Contact Position Arrangement Style:

26 single mating end

# Contact Removability:

Nonremovable single mating end 1st contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Friction

# **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Features Provided:**

Pre-tinned terminal

#### **Terminal Location:**

Back single mating end 1st contact grouping

#### **Contact Material:**

Copper alloy single mating end 1st contact grouping

# **Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

# **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, class

2 federal specification 2nd treatment response single mating end 1st contact grouping

# **Terminal Type:**

Solder well single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping
Guide Design And Location:
D shape socket right-hand at 12 oclock
Insert Material Specification:
Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end
Included Contact Quantity:
20 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.