

View Online at <https://aerobasegroup.com/nsn/5935-01-093-5188>

**Body Style:**

Straight type

**Overall Length:**

Between 4.040 inches and 4.060 inches

**Overall Height:**

Between 0.735 inches and 0.755 inches

**Overall Width:**

Between 0.365 inches and 0.385 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.110 inches and 0.130 inches

**Distance Between Mounting Facility Centers:**

Between 3.790 inches and 3.810 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

26 single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end 1st contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Features Provided:**

Pre-tinned terminal

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end 1st contact grouping

**Terminal Type:**

Solder well single mating end 1st contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end 1st contact grouping

**Guide Design And Location:**

D shape socket right-hand at 12 oclock

**Insert Material Specification:**

Mil-m-14, type gdi-30f or type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

20 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.