NSN 5935-01-093-7902

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-7902

| Body Style: |
|---|
| Straight shape |
| Overall Length: |
| 1.875 inches |
| Overall Width: |
| 0.500 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.152 inches |
| Distance Between Mounting Facility Centers: |
| 1.500 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 9 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Polarization Method: |
| Contact |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Turret single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14 ty sd1-5 military specification single material response single mating end |
| Included Contact Quantity: |
| 9 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |

Precious Material And Weight:

0.009 gold grains, troy and 0.009 silver grains, troy

NSN 5935-01-093-7902

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|-----------------------------|
| Gold and silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-m-14 spec.