## NSN 5935-01-093-8508

**Thread Class:** 

Right-hand **Body Style:** 

**Thread Direction:** 

Straight shape, internal coupling

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-8508

Overall Length:
0.750 inches
Overall Diameter:
0.219 inches
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant
Cable Entrance Diameter:
0.086 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-093-8508

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Shell Material Specification:
Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end or mil-m-14077 military specification single material response
single mating end or I-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.