NSN 5935-01-093-9426

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-093-9426

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand
Body Style:
Rectangular shape
Overall Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.688 inches
Overall Height:
0.797 inches
Overall Width:
0.750 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.469 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
Mating End Quantity: 1
1
1 Contact Position Arrangement Style:
1 Contact Position Arrangement Style: 34 single mating end
Contact Position Arrangement Style: 34 single mating end Contact Removability:
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method:
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method:
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi):
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40 Thread Size:
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40 Thread Size: 0.138 inches and 0.112 inches
Contact Position Arrangement Style: 34 single mating end Contact Removability: Removable single mating end single contact grouping Contact Maximum Current Rating In Amps: 13.0 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method: Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40 Thread Size: 0.138 inches and 0.112 inches Terminal Location:

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-093-9426

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Furnished items - potting form
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.