Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-094-1811

| 2a Freed Direction: Right-hand Right-hand Robber; Ribber; Ribber; Ribber; Robber; Robb | |
|--|--------------------------------------|
| Tread Direction: Right-hand Subder, silicone base Overall Length: 2.188 inches Overall Diameter: 1.250 inches Cable Opening Diameter: 0.500 inches Cable Opening Quantity: 1 Scal Type: Preformed packing Size Designation: 60 Mounting Facility Type And Quantity: 1 Thready Oty Per Inch (tpi): 20 750 inches Material: Aurnium alloy Strate Treatment: Anodize Strafter Teatment: Anodized Thread Seisplantor: Strafter Teatment: Anodized Thread Seisplantor: Strafter Teatment: Anodized Thread Seisplantor: Na Airier Teatment: Anodized Thread Seisplantor: Chaf Direct Teatment: Anodized Thread Seisplantor: Na < | Thread Class: |
| Right-hand Seal Material: Rubber, silicone base Overall Length: 2.188 inches Overall Diameter: 1.250 inches Cable Opening Diameter: 0.500 inches Cable Opening Cuantity: 1 Seal Type: Preformed packing Size Designation: 50 Mouting Facility Type And Quantity: 1 threaded coupling Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodized Thread Series Designator: Indiated Surface Treatment: Anodized Thread Series Designator: Indiated Surface Treatment: Anodized Thread Series Designator: Indiate Surface Treatment: Anodized Thread Series Designator: Indiate Surface Treatment: Anodized Thread Series Designator: Indif | |
| Seal Material: Rubber, silicone base Overall Length: 2.188 inches Overall Diameter: 1.260 inches Cable Opening Diameter: 0.500 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 50 Mutring Facility Type And Quantity: 1 threaded coupling Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Straight type wistrain relief Straight type wistrain relief Straight type wistrain relief Straight type interse Anodized Thread Series Designator: Unef Shelf Life: Na Untof Measure: Na Demilitarization: No Shelf Life: Na Shelf Life: Na Demilitarization: No Sheli Life: | Thread Direction: |
| Rubber, silicone base Overall Length: 2.188 inches Overall Diameter: 1.250 inches Cable Opening Diameter: 0.500 inches Cable Opening Quantity: 1 Seal Type: Preformed packing State Type: Preformed packing State Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 20 Thread Size: 0.750 inches Aurnium alloy Surface Treatment: Anodize Strip type Wistrain relief Surface Treatment: Anodize Stript type Usistrain relief Surface Treatment: Anodize Shelf Life: Na Via Unief Shelf Life: Na Pacilitarization: Via Material: Anodize Shelf Life: Na D | Right-hand |
| Overall Length:2.188 inchesOverall Diameter:1.250 inchesCable Opening Diameter:0.500 inchesCable Opening Quantity:1Seal Type:Preformed packingSize Designation:50Monting Facility Type And Quantity:1 threaded couplingThreaded couplingThreaded couplingAnordizeSurface Treatment:AnordizeStraight type wistrain reliefStraight type wistrain reliefStraight type wistrain reliefInread Series Designator:NaViaInfreid Straight type wistrain reliefSurface Treatment:AnordizePreformed Straight type wistrain reliefSurface Treatment:AnordizeStraight type wistrain reliefSurface Treatment:AnordizePreformed Straignator:NaFire:NaSurface Treatment:AnordizeSurface Treatment:AnordizeStraight type wistrain reliefSurface Treatment:AnordizeSurface Treatment:NaNaSurface Treatment:NaSurface Treatment:NaSurface Treatment:Surface Treatment:Surface Treatment:Surface Treatment:Surface Treatment:Surface Treatment:Surface Treatment:Surface Treatment:Surface Treatment: | Seal Material: |
| 2.188 inches Verall Diameter: 1.250 inches Cable Opening Diameter: 0.500 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Auminum alloy Surface Treatment: Anodize Style Designator: Unef Surface Treatment: Anodize Cable Coupling Thread Series Designator: Unef Surface Treatment: Na | Rubber, silicone base |
| Overall Diameter:1.250 inchesCable Opening Diameter:0.500 inchesCable Opening Quantity:1Sale Designation:Size Designation:50Mounting Facility Type And Quantity:1 threaded couplingThready Quy Per Inch (tpi):20Thread Size:0.750 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStraight type wistrain reliefStraight type wistrain reliefIntread Series Designator:Unit of Measure:NaNaFig:Na | Overall Length: |
| 1.250 inches Cable Opening Diameter: 0.500 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Straight type wistrain relief Surface Treatment: Anodize Thread Selies Designator: Inite of Measure: | 2.188 inches |
| Cable Opening Quantity: Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Threaded coupling Threaded coupling Threaded coupling Autority Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Stright type wistrain relief Stright type wistrain relief Stright type wistrain relief Sheft Life: Nra Life: Na Sheft Life: Na Fine Cable Company Sheft Life: Na Sheft Life: Na Sheft Life: <t< td=""><td>Overall Diameter:</td></t<> | Overall Diameter: |
| 0.500 inches Cable Opening Quantity: 1 Cable Opening Quantity: 1 Freformed packing Seal Type: Preformed packing Size Designation: 50 Munting Facility Type And Quantity: 1 threaded coupling Threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Straight type type type type type type type typ | 1.250 inches |
| Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Auminum alloy Surface Treatment: Anodize Surface Treatment: Anodized Thread Series Designator: Unef Interface Treatment: Anodized Thread Series Designator: Inef Na Finell Life: Na Finell Life: Na Finellitarization: No Fing: | Cable Opening Diameter: |
| 1 Seal Type: Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type wistrain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Dit of Measure: Pomilitarization: No Fig: | 0.500 inches |
| Seal Type:Preformed packingSize Designation:50Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):20Thread Size:0.750 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStraight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:InefSurface Treatment:AnodizedDirtread Series Designator:InefSheff Life:NaPinei Measure:Ini of Measure:Ini of Measure:NoFig: | Cable Opening Quantity: |
| Preformed packing Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig: | 1 |
| Size Designation: 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Stright type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: Na Inter Greatment: Indice Complement Indized Thread Series Designator: Inter Greatment: Indized Thread Series Designator: Inter Greatment: Inter Greatment Inter Gr | Seal Type: |
| 50 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unif Of Measure: Demilitarization: No | Preformed packing |
| Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):20Thread Size:0.750 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:NaDir of Measure:In of Measure: <tr< td=""><td>Size Designation:</td></tr<> | Size Designation: |
| l threaded coupling Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a Fig: | 50 |
| Thready Qty Per Inch (tpi):2020Fhread Size:0.750 inchesMaterial:Auminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aDint of Measure:Ponilitarization:NoFig: | Mounting Facility Type And Quantity: |
| 20 Fhread Size: 0.750 inches Material: Atuminum alloy Auminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Furead Series Designator: Unef Shelf Life: N/a Dint Of Measure: No Fig: | 1 threaded coupling |
| Thread Size:0.750 inchesMaterial:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:NaDenilitarization:InFreiSurface Treatment:Inter Series Designator:Straight type w/strain reliefShelf Life:NaFreiFreiStraight type w/strain reliefStraight type w/strain relie | Thready Qty Per Inch (tpi): |
| 0.750 inches Material: Material: Aluminum alloy Surface Treatment: Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Fmiliatrization: No | 20 |
| Material:Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Denilitarization:NoFig: | Thread Size: |
| Aluminum alloySurface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | 0.750 inches |
| Surface Treatment:AnodizeStyle Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig: | Material: |
| Anodize Style Designator: Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Fig: | Aluminum alloy |
| Style Designator:Straight type w/strain reliefSurface Treatment:AnodizedThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Surface Treatment: |
| Straight type w/strain relief Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Anodize |
| Surface Treatment: Anodized Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No | Style Designator: |
| Anodized Fread Series Designator: Unef Shelf Life: N/a Init Of Measure: Pomilitarization: No Fig: | Straight type w/strain relief |
| Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Surface Treatment: |
| Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No | Anodized |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Series Designator: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Unef |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| Demilitarization: No Fiig: | Unit Of Measure: |
| No Fiig: | - |
| Fiig: | Demilitarization: |
| | No |
| | |
| | A10100 |