Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-094-1873

Tł	nread Class:
28	a
Tł	nread Direction:
Ri	ight-hand
B	ody Style:
St	traight shape
0	verall Length:
Be	etween 7.738 inches and 7.745 inches
0	verall Height:
1.	540 inches
0	verall Width:
0.	640 inches
Di	istance Between Mounting Facility Centers:
6.	950 inches
Tł	nreaded Device Type:
М	ounting stud
М	ating End Quantity:
1	
C	ontact Removability:
R	emovable single mating end single contact grouping
Р	olarization Method:
М	ating end
Tł	nready Qty Per Inch (tpi):
32	2
Tł	nread Size:
0.	138 inches
Te	erminal Location:
Ва	ack single mating end single contact grouping
C	ontact Material:
С	opper alloy single mating end single contact grouping
C	ontact Surface Treatment:
G	old single mating end single contact grouping and nickel single mating end single contact grouping
In	sert Material:
ΡI	astic diallyl phthalate single mating end
C	ontact Surface Treatment Specification:
М	il-g-45204, ty ii, cl i military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal
sp	pecification 2nd treatment response single mating end single contact grouping
Te	erminal Type:
С	rimp single mating end single contact grouping
C	ontact Material Specification:
Q	q-c-533, alloy 25, ht per mil-h-7199a federal specification single material response single mating end single contact grouping
In	sert Material Specification:

Mil-m-14f, type mdg military specification single material response single mating end



Included Contact Quantity: 30 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.