NSN 5935-01-094-2228

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-094-2228

Body Style:
Right angle type
Overall Length:
1.541 inches
Overall Width:
0.494 inches
Body Height:
0.422 inches
Environmental Protection:
Corrosion resistant and moisture proof and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Copper single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:

moert material opecification:

Mil-m-14, ty gdi-30f or sdg-f military specification single material response single mating end

NSN 5935-01-094-2228

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 5 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):