Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-095-3884

nread Class:	
nread Direction:	
ght-hand	
ody Style:	
raight shape w/cable clamp	
verall Length:	
156 inches	
ushing Diameter:	
500 inches	
verall Height:	
688 inches	
verall Width:	
688 inches	
nvironmental Protection:	
leatherproof	
enter To Center Distance Between Mounting Facilities Parallel To Heig	ht:
500 inches	
stance Between Centerlines Of Mounting Facilities Parallel To Body W	vidth:
500 inches	
able Entrance Diameter:	
219 inches	
stance From Mounting Shoulder To Front Face:	
550 inches	
nreaded Device Type:	
ounting hole	
ating End Quantity:	
ontact Position Arrangement Style:	
nc single mating end	
ontact Removability:	
emovable single mating end single contact grouping	
nell Type:	
blid	
onnector Locking Method:	
ayonet pin	
onnector Cable Strain Relief Method:	
ompression nut	
nready Qty Per Inch (tpi):	
)	
nread Size:	

## NSN 5935-01-095-3884

Electrical Receptacle Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Silver **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and body surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0