

View Online at <https://aerobasegroup.com/nsn/5935-01-095-8431>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

3.650 inches

**Overall Height:**

0.550 inches

**Overall Width:**

0.390 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

3.400 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Thread Length:**

0.130 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Nickel single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Qq-n-290, cl 2 federal specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, grade c, class 00 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

56 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Jackscrew type-male and location-right hand and jackscrew type-female and location-left hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.056 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-55302/61 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.