Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-095-9749

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 0.677 inches **Overall Height:** 0.500 inches **Overall Width:** 0.500 inches **Environmental Protection:** Humidity resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.340 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Distance From Mounting Shoulder To Front Face:** 0.375 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Mrap - common nsn - used on 2 mrap variants and 4 other weapon systems. Thready Qty Per Inch (tpi): 36 **Thread Size:**

0.250 inches

Terminal Location:

Back single mating end single contact grouping



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polychlorotrifluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Steel
Shell Material Specification:
Qq-s-764 1st material response clear printed value
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.