Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-095-9751

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
0.875 inches
Overall Height:
0.375 inches
Overall Width:
0.375 inches
Environmental Protection:
Humidity resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.093 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.232 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.232 inches
Distance From Mounting Shoulder To Front Face:
0.375 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Tre	atment:
Gold single mating er	nd single contact grouping
Insert Material:	
Plastic polytetrafluor	pethylene single mating end
Contact Surface Tre	eatment Specification:
Mil-g-45204, type 1,	grade c, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating	end single contact grouping
Contact Material Sp	ecification:
Qq-c-530 federal spe	ecification single material response single mating end single contact grouping
Shell Material:	
Steel	
Shell Material Speci	ification:
Qq-s-764 federal spe	ecification single material response
Insert Material Spec	ification:
Mil-p-19468 military s	specification single material response single mating end
Included Contact Q	uantity:
1 single mating end s	single contact grouping
Included Contact Ty	уре:
Coaxial socket single	e mating end single contact grouping
Precious Material A	nd Location:
Contact surfaces gold	d
Precious Material A	nd Weight:
0.005 gold grains, tro	оу
Precious Material:	
Gold	
Thread Series Desig	gnator:
Uns	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	ndard):
Mil-g-45204 spec.	