

View Online at <https://aerobasegroup.com/nsn/5935-01-096-0027>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Rectangular shape

Overall Length:

2.720 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.281 inches

Overall Width:

1.230 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.766 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

75 single mating end

Polarization Method:

Jackscrew and guide pin/socket

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Bracket

Thready Qty Per Inch (tpi):

32 and 40

Thread Size:

0.138 inches and 0.112 inches

Insert Material:

Plastic phenolic single mating end

Insert Material Specification:

Mil-m-14 ty mfh military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Special Features:

Items furnished as accessories -jackscrew knob

Precious Material And Location:

Guide pin and guide socket surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.