

View Online at <https://aerobasegroup.com/nsn/5935-01-096-0027>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Rectangular shape

**Overall Length:**

2.720 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.281 inches

**Overall Width:**

1.230 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and shock resistant and vibration resistant

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.766 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

75 single mating end

**Polarization Method:**

Jackscrew and guide pin/socket

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Bracket

**Thready Qty Per Inch (tpi):**

32 and 40

**Thread Size:**

0.138 inches and 0.112 inches

**Insert Material:**

Plastic phenolic single mating end

**Insert Material Specification:**

Mil-m-14 ty mfh military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Special Features:**

Items furnished as accessories -jackscrew knob

**Precious Material And Location:**

Guide pin and guide socket surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.