# NSN 5935-01-096-0833

Crimp single mating end single contact grouping

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-096-0833

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.013 inches
Overall Diameter:
0.560 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
28
Thread Size:
0.438 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber silicone class q single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

## NSN 5935-01-096-0833

Electrical Plug Connector - Page 2 of 2



## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Copper alloy

## **Shell Material Specification:**

Qq-b-626 federal specification single material response

#### **Included Contact Quantity:**

1 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:** 

Gold

#### **Thread Series Designator:**

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

## Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.