

View Online at <https://aerobasegroup.com/nsn/5935-01-096-6213>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, flange mount

**Overall Length:**

0.625 inches

**Overall Height:**

0.405 inches

**Environmental Protection:**

Shock proof and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.102 inches

**Distance Between Mounting Facility Centers:**

0.481 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c or d, class 2 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, cond ht federal specification single material response single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Material Specification:**

Qq-s-764 federal specification single material response or mil-t-8504 military specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.