## NSN 5935-01-096-6222

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-096-6222

view Online at https://defobasegroup.com/nsh/0300-01-030-0222
Body Style:
Right angle type
Overall Length:
3.500 inches
Overall Height:
0.550 inches
Overall Width:
0.459 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.250 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Guide Design And Location:
D shape socket left-hand at 6 oclock and d shape pin right-hand at 6 oclock
Insert Material Specification:
Mil-m-14, type gdi-30f or sdg-f military specification single material response single mating end

## **Included Contact Type:**

**Included Contact Quantity:** 

Round pin single mating end single contact grouping

80 single mating end single contact grouping

## NSN 5935-01-096-6222

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.080 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.