Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-096-6240

#### **Thread Class:**

2a and 2b and 2a

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape

# **Overall Length:**

1.350 inches

#### **Overall Height:**

1.090 inches

### **Overall Width:**

0.250 inches

### **Distance Between Mounting Facility Centers:**

1.150 inches

#### **Threaded Device Type:**

Coupling facility and mounting stud

### Mating End Quantity:

1

# **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

### **Connector Locking Method:**

Jackscrew-socket

### Thready Qty Per Inch (tpi):

56

### Thread Size:

0.086 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic polyphenylene single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping



| Pin sing | le mating end single contact grouping   |
|----------|---|
|          | t Material Specification:   |
| Qq-c-53  | 0 federal specification single material response single mating end single contact grouping    |
| Insert N | Naterial Specification:   |
| Mil-m-24 | 4519 military specification single material response single mating end                        |
| Unable   | To Decode:  |
| Unable   | to decode and unable to decode  |
| Include  | d Contact Quantity:   |
| 20 singl | e mating end single contact grouping  |
| Include  | d Contact Type:   |
| Round s  | socket single mating end single contact grouping  |
| Special  | Features:   |
| Jackscr  | ew type-male and location-right hand bottomandjackscrew type-female and location-left hand to |
| Preciou  | is Material And Location:   |
| Contact  | surfaces gold   |
| Preciou  | is Material And Weight:   |
| 0.020 g  | old grains, troy  |
| Preciou  | is Material:  |
| Gold     |   |
| Thread   | Series Designator:  |
| Unc      |   |
| Shelf Li | ife:  |
| N/a      |   |
| Unit Of  | Measure:  |
|          |   |
| Demilita | arization:  |
| No       |   |
| Fiig:    |   |
| A039b0   |   |
| Mil-std  | (military Standard):  |
| Mil-g-45 | 204 spec.   |