Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-096-8016

## **Thread Class:**

2a and 2b

## **Thread Direction:**

Right-hand

## **Body Style:**

Straight shape w/screw locks

### **Overall Length:**

1.250 inches

### **Overall Height:**

1.531 inches

**Overall Width:** 

0.438 inches

## **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

### Threaded Device Type:

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

14 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

### **Polarization Method:**

Jackscrew

## **Connector Locking Method:**

Jackscrew-socket

## Thread Length:

0.320 inches

## Thready Qty Per Inch (tpi):

32

# Thread Size:

0.138 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

NSN 5935-01-096-8016

Electrical Plug Connector - Page 2 of 2



### **Terminal Type:**

Crimp single mating end single contact grouping

### **Included Contact Quantity:**

14 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.013 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unc

### **Specification Data:**

81349-mil-c-28748/3 government specification

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.