

View Online at <https://aerobasegroup.com/nsn/5935-01-096-8538>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling w/strain relief

**Overall Length:**

2.051 inches

**Overall Diameter:**

1.641 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Cable Entrance Diameter:**

0.365 inches

**Distance From Mounting Shoulder To Front Face:**

0.691 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-80 single mating end

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Cable clamp

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.125 inches

**Insert Material:**

Rubber single mating end

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response

**Bushing Accommodation Hole Shape:**

Round w/flat

**Special Features:**

Contact designation 16-95

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0