## NSN 5935-01-096-8842

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-096-8842

Body Style:
Straight shape
Overall Length:
3.350 inches
Overall Height:
0.530 inches
Overall Width:
3.150 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Glass and plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-p-19833 military specification single material response or mil-f-14 military specification single material response single material response or mil-f-14 military specification single material response single material response or mil-f-14 military specification single material response single material response or mil-f-14 military specification single material response or mil
Included Contact Quantity:
60 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Polarizing pins are square posts

Contact surfaces gold

**Precious Material And Location:** 

## NSN 5935-01-096-8842

Electrical Plug Connector - Page 2 of 2



<b>Precious Material And Weight:</b>
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.