

View Online at <https://aerobasegroup.com/nsn/5935-01-096-9388>

Environmental Protection:

Cold resistant and corrosion resistant and heat resistant and humidity resistant and vibration resistant

Mating End Quantity:

1

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

1000.0 megahertz single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-c-14550, class 5 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type ii, class 1, grade c military specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-b-626, composition 22, half hard federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact gold and shield gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-14550 spec.