## NSN 5935-01-097-1773

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-097-1773

Thread Class
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Angle, shape, internal coupling
Overall Length:
1.375 inches
Overall Height:
0.738 inches
Overall Diameter:
0.400 inches
Environmental Protection:
Corrosion resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Cable Entrance Diameter:
0.400 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Crimp type
Thread Length:
0.130 inches
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Side single mating end single contact grouping
Contact Surface Treatment:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Gold single mating end single contact grouping Contact Surface Treatment Specification:

## **NSN 5935-01-097-1773**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Uns
Specification Data:
81349-mil-c-39012/56 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.