

View Online at <https://aerobasegroup.com/nsn/5935-01-097-1786>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.469 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Cable Entrance Diameter:**

Between 0.350 inches and 0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-29 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

2.875 inches

**Distance From Centerline To Cable End:**

3.438 inches

**Thread Length:**

0.664 inches

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 175.0 degrees celsius

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Silicon single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate and nickel

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification 1st treatment response and qq-p-416, type 2, class 3 federal specification 2nd treatment response

**Included Contact Quantity:**

17 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-dtl-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3408 government standard

Significant

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.