## NSN 5935-01-097-3701

Electrical Connector Insert - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-097-3701

**Body Style:** 

Rectangular shape, center screwlock

**Overall Length:** 

2.420 inches

**Overall Height:** 

1.283 inches

**Overall Width:** 

1.350 inches

**Distance Between Mounting Facility Centers:** 

2.045 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

80 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

22.0 single mating end single contact grouping

**Polarization Method:** 

Polarization boss

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type i, grade c or d military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

80 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold

**Precious Material:** 

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5935-01-097-3701

Electrical Connector Insert - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Shelf Life:

Mil-g-45204 spec.